

RECEIVED
CENTRAL FAX CENTER Application Serial No.: 09/986,622
JUN 12 2008 Attorney Docket No.: 09877.0189-00

IN THE SPECIFICATION:

At page 18, line 4:

Fig. 10 schematically depicts a conventional system for drawing an optical fiber ~~402-1002~~ from an optical preform, said system being typically located onto a so-called drawing tower. The drawing system generally comprises a drawing furnace ~~404-1001~~, wherein the bottom of an optical preform is heated at its softening temperature, an apparatus ~~403-1003~~ for measuring the diameter of the drawn fiber ~~402-1002~~, a cooling apparatus ~~404-1004~~ for cooling the fiber before coating it and a coating device ~~405-1005~~ for applying the protective coating onto the fiber. The optical preform is generally connected to moving means for progressively moving the preform downwardly to the heating zone of the furnace while the fiber is being drawn. The coating device may comprise a coating die, containing a liquid curable resin composition (e.g. urethane-acrylate based resin), followed by a UV curing apparatus ~~406-1006~~ (e.g. an UV oven) and by a device ~~407-1007~~ for measuring the diameter of the coated fiber and the concentricity of said coating. When desired, further coating devices may be positioned after the first one, for applying further layers of different coating compositions onto the fiber.